



### SAFETY DATA SHEET

REVISION DATE: 05-14-2015 SUPERSEDES: 05-12-2015

### SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER

### PRODUCT INFORMATION

PRODUCT: FOSTER 40-20

PRODUCT DESCRIPTION: Coating
INTENDED USE: Coating
PRODUCT IDENTIFIER: 827566PM

### COMPANY INFORMATION

H.B. Fuller Company

1200 Willow Lake Boulevard Vadnais Heights, MN 55110

Phone: 888-423-8553

Medical Emergency Phone Number (24 Hours): 1-888-853-1758 Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

# **SECTION 2: HAZARDS IDENTIFICATION**

GHS Hazard Symbols:







GHS Signal Word: Danger

GHS Classification: Skin Sensitisation Category 1; Germ Cell Mutagenicity Category 1B; Carcinogenicity

Category 1B; Hazardous to the aquatic environment - Acute Category 2; Hazardous to

the aquatic environment - Chronic Category 2

GHS Hazard May cause an allergic skin reaction.; May cause genetic defects..; May cause cancer.;

**Phrases:** Toxic to aquatic life...; Toxic to aquatic life with long lasting effects.

**GHS Precautions:** 

Safety Precautions: Obtain special instructions before use. Do not handle until all safety precautions have

been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray.

Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face

protection.

First Aid Measures: IF ON SKIN: Wash with plenty of soap and water. IF exposed or concerned: Get medical

advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Wash

contaminated clothing before reuse. Collect spillage.

Storage: Store locked up.

Disposal: Dispose of contents/container in accordance with local/regional/national/international

regulation for hazardous wastes.

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	PERCENT	Classification	Note
Barium compound	13701-59-2	5 - 10	Acute Tox. 4; H332 Acute Tox. 4; H302	* (see below)
Titanium dioxide	13463-67-7	5 - 10	Carc. 2; H351	* (see below)

FOSTER 40-20 827566PM

### SAFETY DATA SHEET

Zinc oxide	1314-13-2	1 - 5	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	
Iodo-2-propynyl butylcarbamate	55406-53-6	0.1 - 1	Aquatic Acute 1; H400 Acute Tox. 4; H332 Acute Tox. 4; H302 Eye Dam. 1; H318 Skin Sens. 1; H317 STOT SE 3; H335	
Aromatic petroleum distillate	64742-95-6	0.1 - 1	Asp. Tox. 1; H304 Carc. 1B; H350 Muta. 1B; H340	

<sup>\*</sup>This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

### **SECTION 4: FIRST AID MEASURES**

IF IN EYES: Use an eye wash to remove a chemical from your eye regardless of the level of hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing.

IF ON SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

IF INHALED: Remove to fresh air. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

#### **SECTION 5: FIRE FIGHTING MEASURES**

EXTINGUISHING MEDIA:

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Use water spray, foam, dry chemical or carbon dioxide. There is a possibility of pressure buildup in closed containers when heated. Water spray may be used to cool the containers.

SPECIAL FIRE FIGHTING INSTRUCTIONS:

Persons exposed to products of combustion should wear selfcontained breathing apparatus and full protective equipment.

HAZARDOUS COMBUSTION PRODUCTS:

Carbon dioxide, Carbon monoxide Metal fumes

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

SPECIAL PROTECTION: No adverse health effects expected from the clean-up of spilled material.

Follow personal protective equipment recommendations found in

Section 8 of this MSDS.

METHODS FOR CLEAN-UP: Dike if necessary, contain spill with inert absorbent and transfer to

containers for disposal. Keep spilled product out of sewers, watersheds,

or water systems.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

### **SECTION 7: HANDLING AND STORAGE**

Handling:

No special handling instructions due to toxicity.



FOSTER 40-20 827566PM

### SAFETY DATA SHEET

Storage: Store in a cool, dry place. Protect from freezing Consult the Technical Data Sheet for specific storage instructions.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **EXPOSURE LIMITS:**

Chemical Name	Note	ACGIH EXPOSURE LIMITS	OSHA PEL
Calcium carbonate	* (see below)	No data available.	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
Titanium dioxide	* (see below)	10 mg/m3 TWA	15 mg/m3 TWA (total dust)
Zinc oxide		2 mg/m3 TWA (respirable fraction) 10 mg/m3 STEL (respirable fraction)	5 mg/m3 TWA (fume); 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)

<sup>\*</sup>This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

### **ENGINEERING CONTROL METHODS:**

VENTILATION: Use local exhaust ventilation or other engineering controls to

minimize exposures.

EYE PROTECTION: Wear safety glasses when handling this product.

SKIN PROTECTION: Not normally required. Wear chemically resistant gloves to prevent

prolonged or repeated contact.

GLOVES: Not normally required. Use nitrile gloves if conditions warrant.

RESPIRATORY PROTECTION: Respiratory protection may be required to avoid overexposure when

handling this product. Use a respirator if general room ventilation is

not available or sufficient to eliminate symptoms.

Respirators should be selected by and used following requirements

found in OSHA's respirator standard (29 CFR 1910.134).

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

PHYSICAL STATE:

COLOR:

White

ODOR:

Mild Sweet

ODOR THRESHOLD:

PH:

Not established

Not established

FREEZING/MELTING POINT (deg. C):

Not established

BOILING POINT (deg. C):

Not established

Not established

FLASH POINT:

FUND RATE:

Not established

Not established

FLAMMABILITY: Not a flammable solid or gas

UPPER EXPLOSIVE LIMIT (% in air):

LOWER EXPLOSIVE LIMIT (% in air):

VAPOR PRESSURE (mm Hg):

VAPOR DENSITY:

Not established

Not established

Not established

WEIGHT PER GALLON (lbs.): 11.90 SPECIFIC GRAVITY: 1.430

SOLUBILITY: Not established OCTANOL/WATER COEFFICIENT: Not established



FOSTER 40-20 827566PM

### SAFETY DATA SHEET

AUTOIGNITION TEMPERATURE:

DECOMPOSITION TEMPERATURE:

VISCOSITY:

Not established

Not established

No data available.

SOLIDS (% by weight): 69.0 VOC, weight percent 1.76

VOC, U.S. EPA Method 24, less water and exempt

solvents (theoretically determined)

42g/liter of material

### **SECTION 10: STABILITY AND REACTIVITY**

STABILITY: Stable under normal conditions.

CHEMICAL INCOMPATIBILITY: Not established HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide Metal fumes

## **SECTION 11: TOXICOLOGICAL INFORMATION**

**Component Toxicity / Toxicology Data:** 

COMPONENT NAME	LD50/LC50	
Water	ORAL LD50 RAT > 90 ML/KG	
Aluminum hydroxide	ORAL LD50 RAT > 5,000 MG/KG	
Barium compound	ORAL LD50 RAT 530 MG/KG	
-	DERMAL LD50 RABBIT > 2,000.00 MG/KG	
Calcium carbonate	ORAL LD50 RAT 6,450 MG/KG	
Titanium dioxide	ORAL LD50 RAT > 10,000 MG/KG	
Zinc oxide	ORAL LD50 RAT > 5,000 MG/KG	
2,2,4-Trimethyl-1,3-	ORAL LD50 RAT 3,200 MG/KG	
pentanediolmonoisobutyrate	DERMAL LD50 RAT > 15,200.00 MG/KG	

# This product is a mixture. Unless noted, the information below is based on components.

Skin corrosion / irritation: Can cause minor skin irritation, defatting, and dermatitis. Serious eye damage / irritation :Can cause minor irritation, tearing and reddening.

Respiratory / skin sensitization: No data available. Germ cell mutagenicity: May cause genetic defects.

Carcinogenicity: Contains a material that may cause cancer.

Reproductive toxicity: No data available.

Specific target organ toxicity-single exposure: No data available.

Respiratory irritation / Narcotic effects: May cause respiratory irritation.

Specific target organ toxicity-repeated exposure: No data available.

Target organs potentially affected by exposure: Lungs

Aspiration hazard: No data available.

Medical Conditions Aggravated by Exposure: Lung disease

### **SECTION 12: ECOLOGICAL INFORMATION**

OVERVIEW: No ecological information available for this product.



## **SAFETY DATA SHEET**

MOBILITY: No data available. PERSISTENCE: No data available. No data available. **BIOACCUMULATION:** 

### This product has not been tested for ecological effects. Relevant information for components is listed below:

Component:	Ecotoxicity values:	
2,2,4-Trimethyl-1,3-	Acute Toxicity (Fish): 96 Hr LC50 Pimephales promelas: 30 mg/L	
pentanediolmonoisobutyrate	Acute Toxicity (Daphnia): Not established	
	Acute Toxicity (Algae): 72 Hr EC50 Pseudokirchneriella subcapitata: 18.4 mg/L	

#### **SECTION 13: DISPOSAL CONSIDERATIONS**

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.

## **SECTION 14: TRANSPORT INFORMATION**

Consult Bill of Lading for transportation information.

US DOT: **NOT REGULATED** IATA: NOT REGULATED

IMDG: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES,

LIQUID, N.O.S. (ZINC OXIDE), 9, III, MARINE POLLUTANT

## **SECTION 15: REGULATORY INFORMATION**

**INVENTORY STATUS** 

This product is in compliance with the Toxic Substances Control Act's U.S. EPA TSCA:

Inventory requirements.

The components of this product are included on the DSL or are exempt CANADIAN CEPA DSL:

from DSL requirements.

**EUROPEAN REACH:** As a result of the introduction of REACH into Europe, this product

cannot be imported into Europe unless the REACH requirements are

**AUSTRALIA AICS:** This product contains a component that is not on the Australian

Inventory (AICS).

CHINA IECSC INVENTORY: This product is in compliance with the Inventory of Existing Chemical

Substances in China (IECSC) requirements.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at reg.request@hbfuller.com to request an export review.

This product contains a chemical substance that is

1,2-ethanediyl)

subject to a Significant New Use Rule (SNUR)

under Section 5(a)(2) of TSCA:

79 FR 59186, Oct 1, 2014 (Proposed rule)

.alpha.(Nonylphenyl)-.omega.-hydroxy-poly(oxy-

FEDERAL REPORTING **EPA SARA Title III Section 313** 



### SAFETY DATA SHEET

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
Barium compounds	13701-59-2	5 - 10
Zinc compounds	1314-13-2	1 - 5
3-Iodo-2-propynyl butylcarbamate	55406-53-6	0.1 - 1

#### STATE REPORTING

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name/List		CAS	Percent
Titanium dioxide	(Carcinogen)	13463-67-7	5 - 10

## **Substances of Very High Concern (SVHC) Content:**

Unless listed below, this product does not contain SVHC's. tert-Octylphenol, ethoxylated

#### **SECTION 16: OTHER INFORMATION**

SDS VERSION DATE:

05-14-2015

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 0 FLAMMABILITY -- 0 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B.Fuller Construction Products, Inc. from its suppliers, and because H.B.Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B.Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B.Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B.Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.