

1-800-872-3684 • PH: 610-344-0637 • FAX: 1-610-436-4983 www.thesafetyhouse.com

•

THESAFETYHOUSE.COM PART #: CHA0105

SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Chemical Name Mixture CAS No. Mixture

Trade Name AMERICAN ENVIRONMENTAL SPRAY BOND

Product Code M-5575-AMERICAN

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)

Adhesive Product

Uses Advised Against None

Company Identification Spray Products Corporation

1323 Conshohocken Road Plymouth Meeting Pa. 19462

Telephone (610) 277-1010 Fax (610) 277-4390

E-Mail (competent person) <u>johnd@sprayproducts.com</u>

Emergency telephone number

Emergency Phone No. Transportation Emergency: CHEMTREC 24 hr. 1-800-424-

9300 / 1 (703) 527-3887 (Collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)

Flam. Aerosol 1; Liquefied gas; Eye Irrit. 2; Skin Irrit. 2; Repr. 2; STOT SE 3; STOT RE 2; Asp. Tox. 1

Label elements

Hazard Symbol



Signal word(s)

Hazard Statement(s) Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure:

Central Nervous System, Route: Inhalation

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Precautionary Statement(s)

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Avoid breathing spray.

Wear protective gloves/eye protection.

Wash hands and exposed skin after use.

Use only outdoors or in a well-ventilated area.

Protect from sunlight and do not expose to temperatures exceeding 50

°C/122 °F.

Other hazards None

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt. *	CAS No.	Hazard classification		
		· ·	Flam. Liq. 2; H225		
n-Hexane			Asp. Tox. 1; H304		
	25 - 30	110-54-3	Repr. 2; H361		
II-HEXAIIC	25 - 50	110-04-0	Skin Irrit. 2; H315		
		STOT SE 3; H3			
			STOT RE 2; H373		
			Flam. Liq. 2; H225		
Acetone	25 - 30	67-64-1	Eye Irrit. 2; H319		
			STOT SE 3; H336		
Propane	20 - 30	74-98-6	Flam. Gas 1; H220		
Proparie	20 - 30	74-98-6	Liquefied gas; H280		

Additional Information - None

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation

Remove person to fresh air and keep comfortable for breathing. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention.

^{*} The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

Skin Contact Wash affected skin with soap and water. If skin irritation occurs, get

medical advice/attention. Take off contaminated clothing and wash it

before reuse

Eye Contact Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. Get medical

attention if eye irritation develops or persists.

Ingestion Do not give anything by mouth to an unconscious person. Do NOT

induce vomiting. Get medical attention immediately.

Most important symptoms and effects, both acute and

delayed

Aspiration of droplets may cause pulmonary oedema.

Indication of any immediate medical attention and

special treatment needed

IF SWALLOWED: Immediately call a POISON CENTER or

doctor/physician.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

-Suitable Extinguishing Media Extinguish with carbon dioxide, dry chemical, foam or water spray.

-Unsuitable Extinguishing Media Do not use water jet.

Special hazards arising from the substance or

mixture

Highly flammable vapor (flash point below 23°C).

Advice for fire-fighters A self contained breathing apparatus and suitable protective clothing

should be worn in fire conditions. Keep containers cool by spraying

with water if exposed to fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and

emergency procedures

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Avoid contact with skin and eyes. Avoid breathing spray. Wear

protective gloves/eye protection.

Environmental precautions Prevent liquid entering sewers, basements and work pits.

Methods and material for containment and cleaning up Cover spills with inert absorbent material. Transfer to a container for

disposal or recovery.

Reference to other sections None

Additional Information None

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling Keep away from heat/sparks/open flames/hot surfaces. – No

smoking. Avoid contact with skin and eyes. Use product in a well-

ventilated area only. Avoid breathing spray.

Conditions for safe storage, including any incompatibilities

-Storage temperature Keep in a cool, well ventilated place. Protect from sunlight. Store at

temperatures not exceeding 50 °C / 122 °F. Keep container tightly

closed.

-Incompatible materials This product should be stored away from sources of strong heat and

oxidizing chemicals. Also avoid: acids, bases, reducing agents,

peroxides, amines, ammonia, chlorine and halogens.

Specific end use(s) Adhesive Product

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

		(8hr TWA)		(STEL)		
SUBSTANCE.	CAS No.	PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	Note:
Hexane	110-54-3	500 ppm	50 ppm*			*Skin
Acetone	67-64-1	1000	500		750	^NIC
Propane	74-98-6	1000 ppm	Aspyx.#			#

[^]NIC = Notice of Intended Changes (ACGIH®); #Assure minimum oxygen content of work atmosphere.

Recommended monitoring method

NIOSH 1500 (hydrocarbons, B.P. 36 - 126 °C); NIOSH 1300 (Ketones I).

Exposure controls

Appropriate engineering controls

Provide adequate ventilation to ensure that the occupational exposure limit is not exceeded.

Personal protection equipment

Eye/face protection

Wear protective eyewear (goggles, face shield, or safety glasses).



Skin protection (Hand protection/ Other)

Wear suitable gloves if prolonged skin contact is likely. Check with protective equipment manufacturer's data.



Respiratory protection



Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment. Check with

protective equipment manufacturer's data.

Thermal hazards

Not normally required. Use gloves with insulation for thermal

protection, when needed.

Environmental Exposure Controls

None known

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Aerosol spray
Color. Colorless
Odor Not available
Odor Threshold (ppm) Not available
pH (Value) Not available
Melting Point (°C) / Freezing Point (°C) Not available

Boiling point/boiling range (°C):

Flash Point (°C)

Evaporation Rate

Flammability (solid, gas)

Not available

-104 (Propane)

Not available

Extremely flammable aerosol.

Explosive Limit Ranges2.1% - 9.5% v/v (Propane)Vapor pressure (Pascal)ca. 95 x 104 (Propane)Vapor Density (Air=1)ca. 1.56 @ 0°C (Propane)Density (g/ml)Not available

Solubility (Water)

Solubility (Other)

Partition Coefficient (n-Octanol/water)

Auto Ignition Point (°C)

Not available

Not available

450 (Propane)

Decomposition Temperature (°C)

Kinematic Viscosity cSt

Not available

<20.5 @ 40°C

Explosive properties Not explosive.
Oxidizing properties Not oxidizing.
Other information Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity Stable under normal conditions.

Chemical stability Stable.

Possibility of hazardous reactions None anticipated.

Conditions to avoid Avoid contact with heat and ignition sources.

Incompatible materialsThis product should be stored away from sources of strong heat and

oxidizing chemicals. Also avoid: acids, bases, reducing agents,

peroxides, amines, ammonia, chlorine and halogens.

Hazardous decomposition product(s) Forms carbon oxides under fire conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

Information on toxicological effects

n-Hexane (CAS No. 110-54-3):

Acute toxicity Oral: LD50 ≈16 g/kg-bw (May be fatal if swallowed and enters

airways.)

Dermal: LD50 >2 g/kg-bw. rabbit

Inhalation: LC50 > 17600 mg/m3 (Vapor), 24-hr. rat (May cause

drowsiness or dizziness.)

Irritation/Corrosivity Causes skin irritation. Repeated exposure may cause skin dryness

or cracking.

Sensitization It is not a skin sensitizer.

Repeated dose toxicity LOAEL: 37973 mg/kg (101 days, oral, rat, CNS effects)

NOAEL: 1135 mg/kg (101 days, oral, rat, CNS effects)

NOAEC: 1760 mg/m3 (90 day, inhal., female mice, nasal lesions) LOAEC: 3000 ppm (12 hr a day for 16 weeks, inhal., rat, CNS

effects

Carcinogenicity (By analogy with similar materials) NOEL: 31736 mg/m3 (2 years, inhal. Oncogenic effects)

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity There is no evidence of mutagenic potential.

Reproductive toxicity Studies in animals have shown that repeated exposures produce

adverse reproductive effects.

Acetone (CAS No. 67-64-1):

Acute toxicity Oral LD50 = 5800 mg/kg (rat)

Dermal LD50 >15800 mg/kg (rabbit)

Inhalation LC50 76 mg/L (4 hour(s)) (rat) - Vapours may cause

drowsiness and dizziness.

Irritation / Corrosivity Causes serious eye irritation. Repeated exposure may cause skin

dryness or cracking.

Sensitisation It is not a skin sensitiser.

Repeated dose toxicity Oral NOAEL = 900 mg/kg/day (rat) (90-days)

Inhalation NOAEL ≥ 19,000 ppm (rat)

Carcinogenicity It is unlikely to present a carcinogenic hazard to man.

NTP IARC	ACGIH	OSHA	NIOSH
----------	-------	------	-------

No	No	No	No.	No
INO.	110.	INO.	INO.	INO.

MutagenicityNegativeToxicity for reproductionNegativeOther informationNone known.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

n-Hexane (CAS# 110-54-3):

Short term LC50 (96 hour): >1000 µg/L (Oryzias latipes)

LC50 (48 hour): 45 mmol/m3 (Daphnia magna, mortality)

EC50 (96 hour): 2.66% (C. pyreniodosa)

Long Term NOELR (28 days) 2.8 mg/l (Fish) QSAR

NOELR (21 days): 4.88 mg/l (Daphnia magna) QSAR

NOEL (96 hour) 2.077 mg/l (Algae) QSAR

Acetone (CAS No. 67-64-1):

Short term LC50 (96 hour): 5,540 mg/l (Rainbow Trout (Oncorhynchus

mykiss))

LC50 (96 hour): 8,300 mg/l (Bluegill Sunfish (Lepomis

macrochirus))

LC50 (48 hour(s)): 12,600 – 12,700 mg/l (Daphnia magna) EC50 (14 d): 3,020 mg/l (Algae (Chlorella pyrenoidosa) EC50 (15 min): 14,500 mg/l (Bacteria (Photobacterium

phosphoreum)

Long Term Not available.

Persistence and degradability Readily biodegradable.

Bioaccumulative potentialNot available.Mobility in soilNot available.Results of PBT and vPvB assessmentNot available.Other adverse effectsNone known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods Disposal should be in accordance with local, state or national

legislation. Consult an accredited waste disposal contractor or the

local authority for advice.

SECTION 14: TRANSPORT INFORMATION

Sea transport Air transport U.S. DOT (ICAO/IATA) (IMDG) **UN** number 1950 1950 1950 **Proper Shipping Name** Aerosols, flammable Aerosols, flammable Aerosols, flammable Transport hazard class(es) 2.1 2.1 2.1 Packing group Not applicable Not applicable Not applicable **Environmental hazards** None assigned None assigned None assigned Special precautions for user None assigned None assigned None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
n-Hexane	110-54-3	~28	5000
Acetone	67-64-1	~27	5000

SARA 311/312 - Hazard Categories:

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
n-Hexane	110-54-3	~28

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None			

California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
Benzene*	71-43-2	Cancer; Developmental
Methanol*	67-56-1	Developmental

^{*}Trace to none

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: Oct 30, 2015

Hazard Statement(s) and Risk Phrases Listed in: SECTION 2:/ SECTION 3:

Hazard Statement(s)

- H220: Extremely flammable gas.
- H222: Extremely flammable aerosol.
- H225: Highly flammable liquid and vapor.
- H280: Contains gas under pressure; may explode if heated.
- H304: May be fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H336: May cause drowsiness or dizziness.
- H361: Suspected of damaging fertility or the unborn child.
- H373: May cause damage to organs through prolonged or repeated exposure.

Training advice: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.